



**PACIFIC
BLOWERS**



Single Stage Regenerative Blowers

Model	Phase	Motor (HP)	Current (A)@230v	Sound Level (dB)	Rated Pressure (in. H2O)	Rated Vacuum (in. H2O)	Air flow (cfm)	Weight (lbs.)	Curve No.
PB-101	1	0.5	4.5	64	47	40	50	31	4H
PB-201	1	1	6.5	66	47	44	102	46	14H
PB-301	1	2	11.5	75	71	63	141	73	23H
PB-401	1	3	15	75	110	79	141	78	24H
PB-100	3	0.67	2.4	64	51	40	50	26	4H
PB-200	3	1.25	4.2	66	51	47	102	37	12H
PB-300	3	2.35	6.7	75	79	67	141	68	20H
PB-400	3	3.5	8.5	75	118	102	141	73	21H
PB-500	3	3.5	9.5	76	79	87	212	82	30H
PB-600	3	5	14	78	118	110	212	89	31H
PB-700	3	6	17	76	134	130	212	95	32H
PB-800	3	8.5	22	78	110	122	353	318	80H
PB-900	3	11.5	29	78	177	138	353	333	81H
PB-1000	3	15	40	78	248	158	353	366	82H
PB-1100	3	15	40	82	67	71	706	434	100H
PB-1200	3	20	54	82	106	114	706	476	101H
PB-1300	3	30	76	82	169	150	706	505	102H

Double Stage Regenerative Blowers

Model	Phase	Motor (HP)	Current (A)@230v	Sound Level (dB)	Rated Pressure (in. H2O)	Rated Vacuum (in. H2O)	Air flow (cfm)	Weight (lbs.)	Curve No.
PB-102/1	1	0.5	4.5	68	59	40	58	40	6H
PB-202/1	1	1	6.5	68	83	67	58	45	215H
PB-302/1	1	1.5	10	68	98	79	58	51	225H
PB-102	3	0.67	2.4	68	59	40	58	34	37H
PB-202	3	1.2	4.2	68	98	80	58	36	40H
PB-302	3	2	5.9	68	118	87	58	43	41H
PB-402S	3	2.35	6.7	75	110	110	110	78	49H
PB-402	3	3.5	9.5	71	158	118	113	83	50H
PB-502	3	3.5	9.5	78	118	110	145	94	59H
PB-602	3	5	14	78	165	161	145	100	60H
PB-702	3	6	17	78	197	169	145	102	61H
PB-802	3	6	17	80	138	150	215	126	72H
PB-902	3	8.5	22	80	197	170	215	172	73H
PB-1002	3	11.5	29	80	256	177	215	188	74H
PB-1102	3	16.9	43	82	256	170	353	485	91H
PB-1202	3	23.2	59	82	307	181	353	501	92H
PB-1302	3	20	54	88	87	99	776	618	111H
PB-1402	3	25	65	88	118	134	776	651	112H
PB-1502	3	35	82	88	189	189	776	684	113H
PB-1602	3	50	102	88	236	236.22	776	794	114H

The electric motors used in these blowers are AC motor equipped with self-cooling fans and rated as "F" class with IP54 protection. The above specifications may be changed without notice for improved product performance.